

High Pressure Cleaner

Cold water, mobile - Series 4x4

KD1340



Type		KD1340-Standard	KD1340-Premium
Voltage	3/PE/AC/50Hz/415V	▶ 10m HP-Hose DN08 - 315bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Vario-Nozzle ▶ Stainless-Steel Jet-Nozzle 25° ▶ 25l Cleaning-Detergent tank ▶ Detergent-Supply c/w Low-Pressure Injector and Metering-valve	▶ Hose-Reel ▶ 20 m HP-Hose DN08 - 315bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Nozzle-Protection ▶ Stainless-Steel Jet-Nozzle 25° ▶ Spray-Lance 900mm c/w Rotary-Nozzle ▶ 35l Water-Storage tank ▶ Water-Supply separation acc. water reg. ▶ Chemical supply in high-pressure Jet c/w Metering-valve
Operating pressure	30-170bar/3-17MPa		
Max. pressure	190bar/19MPa		
Discharge capacity	300-1.300l/h		
Nozzle size	070		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	7,4kW/13,1A		
Electrical protection	3x16A slow-blowing		
Weight net/with package		89kg/113kg	97kg/121kg
Dimensions device/with package (LxWxH)		980x620x1000mm/1090x630x1120mm	980x620x1000mm/1090x630x1120mm
Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.			
Art. No.		552003	552004