

High Pressure Cleaner

Cold water, mobile - Series 4x4 KD1840





Туре		KD1840-Premium
Voltage	3/PE/AC/50Hz/415V	► Hose-Reel
Operating pressure	30-120bar/3-12MPa	 20 m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 35I Water-Storage tank Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve
Max. pressure	140bar/14MPa	
Discharge capacity	300-1.800l/h	
Nozzle size	150	
Max. Inlet temperature	45°C	
Pump speed	1400rpm	
Connected load	7,4kW/13,1A	
Electrical protection	3x16A slow-blowing	
Weight net/with package		105kg/129kg
Dimensions device/with package (LxWxH)		980x620x1000mm/1090x630x1120mm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switchoff delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.

Art. No.