

High Pressure Cleaner

Cold water, mobile - Series 3x3

KD823 UK



Type		KD823 UK-Standard	KD823 UK-Premium
Voltage	1/N/PE/AC/50Hz/240V	▶ 10m HP-Hose DN08 - 315bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Vario-Nozzle ▶ Stainless-Steel Jet-Nozzle 25° ▶ 15l Cleaning-Detergent tank ▶ Detergent-Supply c/w Low-Pressure Injector and Metering-valve	▶ Hose-Reel ▶ 15m HP-Hose DN08 - 315bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Nozzle-Protection ▶ Stainless-Steel Jet-Nozzle 25° ▶ Spray-Lance 900mm c/w Rotary-Nozzle ▶ 17l Water-Storage tank ▶ Water-Supply separation acc. water reg. ▶ Chemical supply in high-pressure Jet c/w Metering-valve
Operating pressure	30-125bar/3-12,5MPa		
Max. pressure	140bar/14MPa		
Discharge capacity	300-720l/h		
Nozzle size	050		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	3,1kW/12,3A		
Electrical protection	13A slow-blowing		
Weight net/with package		51,8kg/74kg	55,8kg/78kg
Dimensions device/with package (LxWxH)		805x485x950mm/1090x630x1040mm	805x485x950mm/1090x630x1040mm
Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar.			
Art. No.		562003	562004