

High Pressure Cleaner

Cold water, stationary - Series KSM KSM3640 - hot water resistant





Туре		KSM3640	KSM3640-INOX
Voltage Operating pressure Max. pressure Discharge capacity	3/PE/AC/50Hz/415V 30-180bar/3-18MPa 200bar/20MPa 900-3600l/h	 7" Touch-Screen Monitor PLC Controls Siemens S7-1200 Automatic Switch On and Off Control for high-pressure pumps Automatic Stand-By Operation Pressureless pipes in Stand-By Booster-Supply-Pump 60I Water-Storage tank Water-Supply separation acc. water reg. Maintenance interval display 	 Stainless Steel (Food-Safe) 7" Touch-Screen Monitor PLC Controls Siemens S7-1200 Automatic Switch On and Off Control for high-pressure pumps Automatic Stand-By Operation Pressureless pipes in Stand-By Booster-Supply-Pump 60I Water-Storage tank Water-Supply separation acc. water reg.
Nozzle size Max. Inlet temperature	4x050 80°C		
Pump speed Connected load	1400rpm 27,0kW/50A		
Electrical protection Weight net/with package		-	Maintenance interval display
Dimensions device/with package (LxWxH)		2130x800x2090mm/ –	2130x800x2090mm/ –

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainlesssteel), suitable for floor installation, triplex-piston pump with chrome-nickel pump head, hot-water resistant up to 85°c, high-performance ceramic piston, stainless-steel valves, leakage-return, booster-pump for charging the high-pressure pumps (cavitation avoidance), automatic pump-on and shut-off control by plc, total-switch-off between 5 to 600min - adjustable, with leakage-recognition, unloader safety-valve for monitoring, pressureless pipe-system in stand-by mode, robust rotary on-off switch - lockable.

Art. No.