

EJ TFR 220

Page: 1 Compilation date: 22/06/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: EJ TFR 220

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	Electrajet Limited
	Unit J3, Glasgow North Trading Estate
	24 Craigmont Street
	Glasgow
	G20 9BT
	United Kingdom
Tel:	0845 8500 666
Fax:	0141 946 0441
Email:	<u>sales@electrajet.co.uk</u>

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

 Hazard statements:
 H314: Causes severe skin burns and eye damage.

 Signal words:
 Danger

 Hazard pictograms:
 GHS05: Corrosion



Precautionary statements:P260: Do not breathe dust/fumes/gas/mist/vapours/spray.P280: Wear protective gloves/protective clothing/eye protection/face protection.P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

EJ TFR 220

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM ALKYL ETHER SULPHATE - REACH registered number(s): 01-2119488639-16-0020

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
500-234-8	68891-38-3	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	1-10%	
			Aquatic Chronic 3: H412		

ALCOHOL ETHOXYLATE C9-11 WITH 6.5 MOL EO

	-	68439-46-3	- Acute Tox. 4: H302; Eye Dam. 1: H318		1-10%	
SODIUM HYDROXIDE						
	215-185-5	1310-73-2	-	Skin Corr. 1A: H314	1-10%	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Irritation or pain may occur at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: Nausea and stomach pain may occur. There may be vomiting.

Inhalation: No symptoms.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water. Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Water fog.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of nitrogen oxides.

EJ TFR 220

Page: 3

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition.

Suitable packaging: Do not use aluminium containers.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL		
UK	-	2 mg/m3	-	-		

Respirable dust

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Gloves (alkali-resistant).

Eye protection: Safety glasses.

Skin protection: Protective clothing.

EJ TFR 220

Page: 4

Section 9: Physical and chemical properties

9.1. Information on basic physica	0.1. Information on basic physical and chemical properties				
State:	Liquid				
Colour:	Red				
Odour:	Characteristic odour				
Evaporation rate:	No data available.				
Oxidising:	Not applicable.				
Solubility in water:	Highly soluble				
Viscosity:	Non-viscous				
Boiling point/range°C:	>100 Melting point/range	e°C:	No data available.		
Flammability limits %: lower:	No data available. up	per:	No data available.		
Flash point°C:	>93 Part.coeff. n-octanol/wa	ter:	No data available.		
Autoflammability°C:	No data available. Vapour press	ure:	Not applicable.		
Relative density:	1.04 +/- 0.005	pH:	13.5		
VOC g/l:	Not applicable.				

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No data available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Flames.

10.5. Incompatible materials

Materials to avoid: Acids. Alkali earth metals.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic

fumes of nitrogen oxides.

Section 11: Toxicological information

11.1. Information on toxicological effects

SAFETY DATA SHEET EJ TFR 220

Hazardous ingredients:

SODIUM ALKYL ETHER SULPHATE

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

ALCOHOL ETHOXYLATE C9-11 WITH 6.5 MOL EO

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>300<2000	mg/kg

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:Irritation or pain may occur at the site of contact.Eye contact:There may be irritation and pain.Ingestion:Nausea and stomach pain may occur. There may be vomiting.Inhalation:No symptoms.Delayed / immediate effects:No data available.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM ALKYL ETHER SULPHATE

ALGAE	48H EC50	27,7	mg/l
DAPHNIA	48H EC50	7,4	mg/l
FISH	96H LC50	7,1	mg/l

ALCOHOL ETHOXYLATE C9-11 WITH 6.5 MOL EO

FISH	96H LC50	1-10	mg/l	
				-

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

EJ TFR 220

Page: 6

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding

disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: I

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: E

Transport category: 1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

EJ TFR 220

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

Page: 7

H314: Causes severe skin burns and eye damage. H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.