

EJ TFR 7-1 SUPER CONCENTRATE TRAFFIC FILM REMOVER

Page: 1

Compilation date: 12/04/2016

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: EJ TFR 7-1 SUPER CONCENTRATE TRAFFIC FILM REMOVER

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Electrajet Limited

Unit J3, Glasgow North Trading Estate

24 Craigmont Street

Glasgow G20 9BT

United Kingdom

Tel: 0845 8500 666 **Fax:** 0141 946 0441

Email: sales@electrajet.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/. P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

EJ TFR 7-1 SUPER CONCENTRATE TRAFFIC FILM REMOVER

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LAURYL BETAINE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
266-368-1	66455-29-6	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	10-30%
SODIUM ALK	YL ETHER SULPH): 01-2119488639-16-0020	
500-234-8	68891-38-3	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Aquatic Chronic 3: H412	10-30%
SODIUM XYL	ENE SULPHONA	ΓΕ 30% - REACH registered number	r(s): 01-2119513350-56-0001	'
215-090-9	1300-72-7	-	Eye Irrit. 2: H319	10-30%
SODIUM HYI	OROXIDE			
215-185-5	1310-73-2	-	Skin Corr. 1A: H314	10-30%
ALKYL POLY	GLYCOSIDE			
500-220-1	68515-73-1	-	Eye Dam. 1: H318	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear

immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or

longer if substance is still on skin. Consult a doctor. Transfer to hospital if there are burns or symptoms

of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Consult a doctor.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Wash out mouth

with water. Consult a doctor. Transfer to hospital as soon as possible.

Inhalation: May cause sore throat - remove affetced person to fresh air. Seek medical advice if soreness persists.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Severe burns may occur.

Eye contact: Corneal burns may occur.

Ingestion: Corrosive burns may appear around the lips. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat if inhaled directly in confined/poorly ventilated space.

EJ TFR 7-1 SUPER CONCENTRATE TRAFFIC FILM REMOVER

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water. Water spray. Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Water fog.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and

eves.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water. Transfer to a

suitable container.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed. Avoid contact with acids.

Suitable packaging: Keep in original containers

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

EJ TFR 7-1 SUPER CONCENTRATE TRAFFIC FILM REMOVER

Page: 4

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: If ventilation is poor, ensure suitable respiratory protection is available.

Hand protection: Protective gloves. PVC gloves. Rubber gloves.
 Eye protection: Wear suitable tightly fitting goggles or face shield.
 Skin protection: Wear suitable protective clothing - alkali resistant

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Gold-brown

Odour: Characteristic odour

Solubility in water: Highly soluble

Viscosity: Viscous

Boiling point/range°C: >100 Melting point/range°C: No data available.

Flammability limits %: lower: Not applicable. upper: Not applicable.

Flash point°C: Not applicable.

Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable.

Vapour pressure: Not applicable.

Relative density: 1.08 pH: 14

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Intense heat and/or flames

EJ TFR 7-1 SUPER CONCENTRATE TRAFFIC FILM REMOVER

Page: 5

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Chloro-hydrocarbons

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic

fumes of nitrogen oxides.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

LAURYL BETAINE

ORAL	RAT	LD50	>2000	mg/kg
				0 0

SODIUM ALKYL ETHER SULPHATE

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

SODIUM XYLENE SULPHONATE 30%

DERMAL	RBT	LD50	2000	mg/kg
ORAL	RAT	LD50	7200	mg/kg

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

ALKYL POLY GLYCOSIDE

DERMAL	RAT	LD50	>2.000	mg/kg
ORAL	RAT	LD50	>2.000	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Severe burns may occur.

Eye contact: Corneal burns may occur.

Ingestion: Corrosive burns may appear around the lips. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat if inhaled directly in confined/poorly ventilated space.

EJ TFR 7-1 SUPER CONCENTRATE TRAFFIC FILM REMOVER

Page: 6

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM ALKYL ETHER SULPHATE

ALGAE	48H EC50	27,7	mg/l
DAPHNIA	48H EC50	7,4	mg/l
FISH	96H LC50	7,1	mg/l

SODIUM XYLENE SULPHONATE 30%

DAPHNIA	48H EC50	1000	mg/l
FISH	96H LC50	1000	mg/l
GREEN ALGA (Selenastrum capricornutum)	96H LC50	230	mg/l

ALKYL POLY GLYCOSIDE

Daphnia magna	48H EC50	>100	mg/l
FISH	96H LC50	126	mg/l

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Soluble in water. Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

EJ TFR 7-1 SUPER CONCENTRATE TRAFFIC FILM REMOVER

Page: 7

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: I

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Tunnel code: E **Transport category:** 1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be

used only as a guide. This company shall not be held liable for any damage resulting from handling or

from contact with the above product.