

	ALL ELECTRIC MACHINES OFFER UP TO 50% REDUCTION IN RUNNING COST COMPARED TO THE ALTERNATE DIESEL MACHINE				
	SERS1 12kW	SERS2 18kW	SERS3 24kW	SERS4 30kW	SERS5 36kW
Voltage	Three-phase 415v	Three-phase 415v	Three-phase 415v	Three-phase 415v	Three-phase 415v
Load	3 x 20 A	3 x 32 A	3 x 45 A	3 x 54 A	3 x 62 A
Water Flow	13 l/min	13 l/min	13 l/min	13 or 15 l/min	13 , 15 or 21 l/min
Output Pressure	150bar / 2000psi	150bar / 2000psi	150bar / 2000psi	150bar / 2000psi 170bar / 2500psi	150bar / 2000psi 170bar / 2500psi 200bar / 3000psi
Max Temperature	55°C	55°C	55°C	55°C	55°C or 80°C
Motor	5.5hp / 4kW	5.5hp / 4kW	5.5hp / 4kW	5.5hp / 4kW 7hp / 5.5kW	5.5hp / 4kW 7hp / 5.5kW 10hp / 7.5kW
Water Tank Capacity	140ltr Hot 40ltr Cold	140ltr Hot 40ltr Cold	140ltr Hot 40ltr Cold	140ltr Hot 40ltr Cold	140ltr Hot 40ltr Cold